

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
19 April 2001 (19.04.2001)

PCT

(10) International Publication Number  
**WO 01/27584 A1**

- (51) International Patent Classification<sup>7</sup>: **G01L 3/10**
- (21) International Application Number: PCT/EP00/10022
- (22) International Filing Date: 10 October 2000 (10.10.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
9924046.7 11 October 1999 (11.10.1999) GB
- (71) Applicant (for all designated States except US): **FAST TECHNOLOGY GMBH**. [DE/DE]; Otto Hahn Str. 24, Gewerbegebiet Riemerling, 85521 Ottobrunn (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **MAY, Lutz, Axel** [DE/DE]; Wolfratshauser Strasse 23a, 82538 Götting (DE).
- (74) Agent: **BLUFF, John, William**; Lloyd Wise, Tregear & Co., Commonwealth House, 1-19 New Oxford Street, London WC1A 1LW (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- With international search report.
  - Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TORQUE MEASUREMENT APPARATUS



(57) Abstract: Torque in a shaft (61) is detected by means of non-contacting sensors (23, 24) sensing a torque-dependent magnetic field emanated by an integral transducer region (64, 32) of the shaft (61) that is circumferentially or longitudinally magnetised. The shaft (61) is driven by a motor (63) and subject to a longitudinal magnetic field (60) which acts on interference field. In one implementation of the invention coils (L1, L2: L3, L4) are energised to provide a counteracting magnetic field to compensate the interference field (60).

WO 01/27584 A1